SAFETY DATA SHEET



Magnetized Materials

Section 1. Identification

This product is considered an article. This Material Safety Data Sheet is written based on the encapsulated substance or mixture in this article.

 1.1 Product identifier

 Product name : Fiber AOM Laser Head

 Part No. : N1211A, N1211B:

 Validation date: 11/12/2020

 1.2 Relevant identified uses of the substance or mixture and uses advised against

 Material uses : Analytical chemistry.

 1.3 Details of the supplier of the safety data sheet

 Supplier/Manufacturer
 : Keysight Technologies, Inc.

: Keysight Technologies, Inc. 1400 Fountaingrove Parkway Santa Rosa, California 95403

	1.4 Emergency telephone number in case of emergency	: (707) 577-3000
--	---	------------------

Monday - Friday 8:00 - 5:00

Section 2. Hazards identification

This article, when used under reasonable conditions and in accordance with the directions for use, should not present a health hazard. The substance or mixture is encapsulated in the article. Only if released due to use or processing of the article in a manner not in accordance with the product's directions for use it may present potential health and safety hazards.

2.1 Classification of the substance or mixture

OSHA/HCS status: This material is considered hazardous by the OSHA Hazard Communication Standard (29 CFR 1910.1200).

Classification of the substance o	r mixture
H334	RESPIRATORY SENSITIZATION - Category 1
H317	SKIN SENSITIZATION - Category 1
H351	CARCINOGENICITY - Category 2
H372	SPECIFIC TARGET ORGAN TOXICITY (REPEATED EXPOSURE) - Category 1

Ingredients of unknown toxicity: Percentage of the mixture consisting of ingredient(s) of unknown toxicity: 59%

2.2 GHS label elements

Hazard pictograms



Signal word: Danger

Hazard statements

H334 - May cause allergy or asthma symptoms or breathing difficulties if inhaled.

- H317 May cause an allergic skin reaction.
- H351 Suspected of causing cancer.
- H372 Causes damage to organs through prolonged or repeated exposure.

Magnetized Materials

Section 2. Hazards identification

Precautionary statements :

Prevention	 P201 - Obtain special instructions before use. P202 - Do not handle until all safety precautions have been read and understood. P281 - Use personal protective equipment as required. P280 - Wear protective gloves. P285 - In case of inadequate ventilation wear respiratory protection. P260 - Do not breathe dust. P270 - Do not eat, drink or smoke when using this product. P264 - Wash hands thoroughly after handling.
Response	 P272 - Contaminated work clothing should not be allowed out of the workplace. P314 - Get medical attention if you feel unwell. P308 + P313 - IF exposed or concerned: Get medical attention. P304 + P341 - IF INHALED: If breathing is difficult, remove victim to fresh air and keep at rest in a position comfortable for breathing. P342 + P311 - If experiencing respiratory symptoms: Call a POISON CENTER or physician. P302 + P352 + P363 - IF ON SKIN: Wash with plenty of soap and water. Wash contaminated clothing before reuse. P333 + P313 - If skin irritation or rash occurs: Get medical attention.
Storage	Press - Store locked up.
Disposal	: P501 - Dispose of contents and container in accordance with all local, regional, national and international regulations.
2.3 Other hazards Hazards not otherwise	: None known.

classified

Section 3. Composition/information on ingredients

This article, when used under reasonable conditions and in accordance with the directions for use, should not present a health hazard. The substance or mixture is encapsulated in the article. Only if released due to use or processing of the article in a manner not in accordance with the product's directions for use it may present potential health and safety hazards.

Substance/mixture: Mixture (encapsulated in article)

Ingredient name	%	CAS number
Cobalt	10 - 30	7440-48-4
Nickel	10 - 30	7440-02-0
Aluminum	5 - 10	7429-90-5
Copper	1 - 5	7440-50-8

Magnetized materials are usually ferrous metallic items that produce a non-operating gaussian interference reading and have the potential to cause compass deflection in aircraft equipped with non-electrical navigation equipment.

Any concentration shown as a range is to protect confidentiality or is due to batch variation.

There are no ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment and hence require reporting in this section.

Occupational exposure limits, if available, are listed in Section 8.

Section 4. First aid measures

4.1 Description of necessary first aid measures:

Eye contact: Immediately flush eyes with plenty water, occasionally lifting the upper and lower eyelids. Check for and remove any contact lenses Continue to rinse for at least 10 minutes. Get medical attention.

Date of issue : 2/15 04/05/2017 Magnetized Materials Section 4. First aid measures Inhalation Remove victim to fresh air and keep at rest in a position comfortable for breathing. If it 2 is suspected that fumes are still present, the rescuer should wear an appropriate mask or self-contained breathing apparatus. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Get medical attention. If necessary, call a poison center or physician. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband. In the event of any complaints or symptoms, avoid further exposure. Skin contact Wash with plenty of soap and water. Remove contaminated clothing and shoes. Wash contaminated clothing thoroughly with water before removing it, or wear gloves. Continue to rinse for at least 10 minutes. Get medical attention. In the event of any complaints or symptoms, avoid further exposure. Wash clothing before reuse. Clean shoes thoroughly before reuse. Ingestion : Wash out mouth with water. Remove dentures if any. Remove victim to fresh air and keep at rest in a position comfortable for breathing. If material has been swallowed and the exposed person is conscious, give small quantities of water to drink. Stop if the exposed person feels sick as vomiting may be dangerous. Do not induce vomiting unless directed to do so by medical personnel. If vomiting occurs, the head should be kept low so that vomit does not enter the lungs. Get medical attention. Never give anything by mouth to an unconscious person. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband.

4.2 Most important symptoms/effects, acute and delayed

Potential acute health effect	<u>cts</u>
Eye contact	: No known significant effects or critical hazards.
Inhalation	: May cause allergy or asthma symptoms or breathing difficulties if inhaled.
Skin contact	: May cause an allergic skin reaction.
Ingestion : No known s signs/symptoms	ignificant effects or critical hazards. Over-exposure
Eye contact	: No specific data.
Inhalation	: Adverse symptoms may include the following: wheezing and breathing difficulties asthma
Skin contact	: Adverse symptoms may include the following: irritation redness
Induction	: No specific data.
4.3 Indication of immediate	modical attention and special treatment needed, if necessary
Notes to physician	 Treat symptomatically. Contact poison treatment specialist immediately if large quantities have been ingested or inhaled.
Specific treatments	No specific treatment.
Protection of first-aiders	: No action shall be taken involving any personal risk or without suitable training. If it is suspected that fumes are still present, the rescuer should wear an appropriate mask or self-contained breathing apparatus. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Wash contaminated clothing thoroughly with water before removing it, or wear gloves.
Soo tovicological informati	on (Soction 11)

See toxicological information (Section 11)

Section 5. Fire-fighting measures

	J
5.1 Extinguishing media	
Suitable extinguishing medi	a: Use an extinguishing agent suitable for the surrounding fire.
Unsuitable extinguishing	: None known.
media	
5.2 Special hazards arising fro	om the substance or mixture
Specific hazards arising	: No specific fire or explosion hazard.
from the chemical	
Hazardous thermal	: Decomposition products may include the following materials:
decomposition products	metal oxide/oxides
5.3 Advice for fire fighters'	
Special protective actions	: Promptly isolate the scene by removing all persons from the vicinity of the incident if
for fire-fighters	there is a fire. No action shall be taken involving any personal risk or without suitable
-	training.
Special protective equipment	t: Fire-fighters should wear appropriate protective equipment and self-contained breathing
for fire-fighters	apparatus (SCBA) with a full face-piece operated in positive pressure mode.
Section 6. Accidental	release measures
6.1 Personal precautions, pro	tective equipment and emergency procedures
For non-emergency personnel	: No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilled material. Provide adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Put on appropriate personal protective equipment.
For emergency responders	: If specialised clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also the information in "For nonemergency personnel".
6.2 Environmental	: Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains
precautions	and sewers. Inform the relevant authorities if the product has caused environmental
	pollution (sewers, waterways, soil or air).
6.3 Methods and materials for	<u>containment and cleaning up</u>

Move containers from spill area. Avoid dust generation. Do not dry sweep. Vacuum dust with equipment fitted with a HEPA filter and place in a closed, labeled waste container. Place spilled material in a designated, labeled waste container. Dispose of via a licensed waste disposal contractor.

Section 7. Handling and storage

7.1 Precautions for safe ha	<u>ndling</u>
Protective measures	: Put on appropriate personal protective equipment (see Section 8). Persons with a history of skin sensitization problems or asthma, allergies or chronic or recurrent respiratory disease should not be employed in any process in which this product is used. Avoid exposure - obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Do not get in eyes or on skin or clothing. Do not ingest. Use only with adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Keep in the original container or an approved alternative made from a compatible material, kept tightly closed when not in use. Empty containers retain product residue and can be hazardous. Do not reuse container.
Magnetized Materials	

Section 7. Handling and storage

Advice on general occupational hygiene	: Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. Remove contaminated clothing and protective equipment before entering eating areas. See also Section 8 for additional information on hygiene measures.
7.2 Conditions for safe storage, including any incompatibilities	: Store in accordance with local regulations. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10) and food and drink. Store locked up. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabeled containers. Use appropriate containment to avoid environmental contamination.
7.3 Specific end use(s) Recommendations Industrial sector specific solutions	: Industrial applications, Professional applications. : Not applicable.

Section 8. Exposure controls/personal protection

Since the hazardous ingredient in this article is encapsulated, the risk of exposure by inhalation, ingestion, skin contact and

eyes contact is minimum.

8.1 Control parameters

Occupational exposure limits

Ingredient name	Exposure limits
Cobalt	ACGIH TLV (United States, 6/2013).
	TWA: 0.02 mg/m ³ , (as Co) 8 hours.
	OSHA PEL 1989 (United States, 3/1989).
	TWA: 0.05 mg/m ³ , (as Co) 8 hours.
	NIOSH REL (United States, 10/2013).
	TWA: 0.05 mg/m ³ , (as Co) 10 hours. Form:
	Dust and fumes
	OSHA PEL (United States, 2/2013).
	TWA: 0.1 mg/m ³ , (as Co) 8 hours.
Nickel	OSHA PEL 1989 (United States, 3/1989).
	TWA: 1 mg/m ³ , (as Ni) 8 hours.
	NIOSH REL (United States, 10/2013).
	TWA: 0.015 mg/m ³ , (as Ni) 10 hours.
	ACGIH TLV (United States, 6/2013).
	TWA: 1.5 mg/m ³ 8 hours. Form: Inhalable
	fraction
	OSHA PEL (United States, 2/2013).
	TWA: 1 mg/m ³ , (as Ni) 8 hours.

Aluminium	OSHA PEL 1989 (United States, 3/1989).
	Notes: as Al
	TWA: 15 mg/m ³ , (as Al) 8 hours. Form: Dust
	TWA: 5 mg/m ³ , (as Al) 8 hours. Form:
	Pyrophoric
	TWA: 5 mg/m ³ , (as AI) 8 hours. Form:
	Respirable fraction
	TWA: 5 mg/m ³ , (as AI) 8 hours. Form:
	Welding fume
	OSHA PEL (United States, 2/2013). Notes:
	as Al
	TWA: 15 mg/m ³ , (as Al) 8 hours. Form: Total

Section 8. Exposure controls/personal protection

dustNIOSH REL (United States, 10/2013)TWA: 5 mg/m³ 10 hours. Form: RespfractionTWA: 10 mg/m³ 10 hours. Form: TotaACGIH TLV (United States, 6/2013).TWA: 1 mg/m³ 8 hours. Form: RespirfractionOSHA PEL (United States, 2/2013).TWA: 5 mg/m³, (as Al) 8 hours. Form:Respirable fractionACGIH TLV (United States, 6/2013).TWA: 5 mg/m³, (as Al) 8 hours. Form:Respirable fractionACGIH TLV (United States, 6/2013).TWA: 1 mg/m³, (as Cu) 8 hours. Formas CuTWA: 1 mg/m³, (as Cu) 8 hours. Formand mistOSHA PEL 1989 (United States, 3/19Notes: as CuTWA: 1 mg/m³, (as Cu) 8 hours. FormTWA: 1 mg/m³, (as Cu) 8 hours. Form
Copper ACGIH TLV (United States, 6/2013). as Cu TWA: 1 mg/m³, (as Cu) 8 hours. Form and mist OSHA PEL 1989 (United States, 3/19 Notes: as Cu TWA: 1 mg/m³, (as Cu) 8 hours. Form Dusts and Miste
TWA: 0.1 mg/m ³ , (as Cu) 8 hours. Fo Fume NIOSH REL (United States, 10/2013). TWA: 1 mg/m ³ , (as Cu) 10 hours. For Dusts and Mists OSHA PEL (United States, 2/2013). TWA: 1 mg/m ³ 8 hours. Form: Dusts a Mists TWA: 0.1 mg/m ³ 8 hours. Form: Fumo ACGIH TLV (United States, 6/2013). TWA: 0.2 mg/m ³ 8 hours. Form: Fumo

8.2 Exposure controls

controls

: Use only with adequate ventilation. If user operations generate dust, fumes, gas, vapor Appropriate engineering

or mist, use process enclosures, local exhaust ventilation or other engineering controls to keep worker exposure to airborne

contaminants below any recommended or statutory limits.

Environmental exposure : Emissions from ventilation or work process equipment should be checked to ensure controls

they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or

engineering

modifications to the process equipment will be necessary to reduce emissions to acceptable levels.

Individual protection measure	<u>S</u>
Hygiene measures: eating,	: Wash hands, forearms and face thoroughly after handling chemical products, before
	smoking and using the lavatory and at the end of the working period. Appropriate
techniques	
	should be used to remove potentially contaminated clothing. Contaminated work
clothing	
	should not be allowed out of the workplace. Wash contaminated clothing before
reusing.	
	Ensure that eyewash stations and safety showers are close to the workstation location.
Eye/face protection:	: Safety eyewear complying with an approved standard should be used when a risk assessment indicates
	this is necessary to avoid exposure to liquid splashes, mists, gases or dusts. If contact is possible,
	the following protection should be worn, unless the assessment indicates a higher degree of protection:
	safety glasses with side shields.

Skin protection

Magnetized Materials

Section 8. Exposure controls/personal protection

Hand protection	: Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary. Considering the parameters specified by the glove manufacturer, check during use that the gloves are still retaining their protective properties. It should be noted that the time to breakthrough for any glove material may be different for different glove manufacturers. In the case of mixtures, consisting of several substances, the protection time of the gloves cannot be accurately estimated.
Body protection	 Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.
Other skin	: Appropriate footwear and any additional skin protection measures should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.
protection	: Use a properly fitted, particulate filter respirator complying with an approved standard if a risk assessment indicates this is necessary. Respirator selection must be based on known or anticipated exposure levels, the bazards of the product and the safe working limits of the selected
Respiratory protection	respirator.

Section 9. Physical and chemical properties

9.1 Information on basic and chemical properties

Appearance		Solid.
Physical state		Not available.
Color		Odorless.
Odor		Not available.
Odor		Not available.
threshold		Not available.
рН		Not available.
Melting point		Not available.
Boiling point		Not available.
Flash point		Not available.
Evaporation rate		Not available.
Flammability (solid,		
gas)		Not available.
Lower and upper		Not
explosive		available.
(flammable) limits		Not
Vapor pressure		available.
Vapor density		Insoluble in the following materials: cold water and hot
Relative density		water. Not available.
Solubility		Not available.
Solubility in water		
Partition coefficient:	n-	Not available.
octanol/water		Not available.
Auto-ignition temperature		Not available.
Decomposition temperature		
Viscosity		
Date of issue:	11/12/2020	

Section 10. Stability and reactivity

7/15

10.1 Reactivity	:	No specific test data related to reactivity available for this product or its ingredients.
10.2 Chemical stability	:	The product is stable.
10.3 Possibility of hazardous reactions	:	Under normal conditions of storage and use, hazardous reactions will not occur.
10.4 Conditions to avoid	:	No specific data.
10.5 Incompatible materials	:	Reactive or incompatible with the following materials: oxidizing materials, acids and moisture.
	:	Under normal conditions of storage and use, hazardous decomposition products should not be produced.
10.6 Hazardous		
all a survey a stitle in		

decomposition

products

Section 11. Toxicological information

11.1 Information on toxicological effects Acute toxicity

Product/ingredient name	Result	Species	Dose	Exposure
Cobalt	LD50 Oral	Rat	6170 mg/kg	-
Nickel	LD50 Oral	Rat	>9000 mg/kg	-

Irritation/Corrosion

Not available.

Sensitization

Not available.

Mutagenicity

Not available.

Carcinogenicity

Not available.

Classification

Product/ingredient name	OSHA	IARC	NTP
Cobalt	-	2B	-
Nickel	-	2B	Reasonably anticipated to be a human carcinogen.

Reproductive toxicity

Not available.

Teratogenicity

Not available.

Specific target organ toxicity (single exposure)

Not available.

Specific target organ toxicity (repeated exposure) Not available.

Information on the likely routes of exposure

: Routes of entry anticipated: Oral, Dermal, Inhalation.

Potential acute health effectsEye contact: No known significant effects or critical hazards.Inhalation: May cause allergy or asthma symptoms or breathing difficulties if inhaled.Skin contact: May cause an allergic skin reaction.

Ingestion

: No known significant effects or critical hazards.

Symptoms related to the physical, chemical and toxicological characteristics

Eye contact	: No specific data.
Inhalation	: Adverse symptoms may include the following: wheezing and breathing difficulties asthma
Skin contact	: Adverse symptoms may include the following: irritation redness

Ingest	ion	: No	specific	data
		. 140	sp	Come

Delayed and immediate effects and also chronic effects from short and long term exposure Short term exposure Potential immediate : Not available. effects **Potential delayed effects** : Not available. Long term exposure **Potential immediate** : Not available. effects Potential delayed effects : Not available. Potential chronic health effects Not available. General : Causes damage to organs through prolonged or repeated exposure. Once sensitized, a severe allergic reaction may occur when subsequently exposed to very low levels. : Suspected of causing cancer. Risk of cancer depends on duration and level of exposure. Carcinogenicity **Mutagenicity** : No known significant effects or critical hazards. **Teratogenicity** : No known significant effects or critical hazards. **Developmental effects** : No known significant effects or critical hazards. **Fertility effects** : No known significant effects or critical hazards.

Section 11. Toxicological information

Magnetized Materials

12.1 Toxicity

Numerical measures of toxicity Acute toxicity estimates: Not available.

Section 12. Ecological information

Product/ingredient name	Result	Species	Exposure
Cobalt	Acute LC50 4400 μg/l	Daphnia - Daphnia magna	48 hours
	Acute LC50 3.4 mg/l Fresh water	Fish - Pimephales promelas	96 hours
Nickel	Acute EC50 2 ppm Marine water	Algae - Macrocystis pyrifera - Young	4 days
	Acute EC50 450 μg/l Fresh water	Aquatic plants - Lemna minor	4 days
	Acute EC50 1000 μg/l Marine water	Daphnia - Daphnia magna	48 hours
	Acute IC50 0.31 mg/l Marine water	Crustaceans - Americamysis bahia - Juvenile (Fledgling, Hatchling, Weanling)	48 hours
	Acute LC50 47.5 ng/L Fresh water	Fish - Heteropneustes fossilis	96 hours
	Chronic NOEC 100 mg/l Marine water	Algae - Glenodinium halli	72 hours
	Chronic NOEC 3.5 µg/l Fresh water	Fish - Cyprinus carpio	4 weeks
Aluminium	Acute LC50 38000 μg/l Acute LC50 120 μg/l Fresh water	Daphnia - Daphnia magna Fish - Oncorhynchus mykiss Embryo	48 hours 96 hours
	Chronic NOEC 9 mg/l Fresh water	Aquatic plants - Ceratophyllum demersum	3 days
Copper	Acute EC50 1100 µg/l Fresh water	Aquatic plants - Lemna minor	4 days
	Acute EC50 2.1 µg/l Fresh water	Daphnia - Daphnia longispina Juvenile (Fledgling, Hatchling, Weanling)	48 hours
	Acute IC50 13 µg/l Fresh water	Algae - Pseudokirchneriella subcapitata - Exponential growth phase	72 hours
	Acute IC50 5.4 mg/l Marine water	Aquatic plants - Plantae -	72 hours
	Acute LC50 0.072 μg/l Marine water	Crustaceans - Amphipoda - Adult	48 hours
	Acute LC50 7.56 μg/l Marine water	Fish - Periophthalmus waltoni Adult	96 hours
	Chronic NOEC 2.5 µg/l Marine water	Algae - Nitzschia closterium Exponential growth phase	72 hours
	Chronic NOEC 7 mg/l Fresh water	Aquatic plants - Ceratophyllum demersum	3 days

Chronic NOEC 0.02 mg/l Fresh water Chronic NOEC 2 µg/l Fresh water	Crustaceans - Cambarus bartonii - Mature Daphnia - Daphnia magna	21 days 21 days
Chronic NOEC 0.8 µg/l Fresh water	Fish - Oreochromis niloticus Juvenile (Fledgling, Hatchling, Weanling)	6 weeks

12.2 Persistence and degradability

Conclusion/Summary : Ferrous alloy leachate may cause hazardous conditions in groundwater, avoid landfill disposal of used and unused metals.

12.3 Bioaccumulative potential

coefficient (Koc)

Magnetized Materials					
Section 12. Ecological information					
Product/ingredient name	LogPow	BCF	Potential		
Cobalt	-	15600	high		
12.4 Mobility in soil Soil/water partition	: Not available.				

12.5 Other adverse effects : No known significant effects or critical hazards.

Section 13. Disposal considerations

13.1 Waste treatment methods	
Disposal methods	: The generation of waste should be avoided or minimized wherever possible. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible. This material and its container must be disposed of in a safe way. Care should be taken when handling emptied containers that have not been cleaned or rinsed out. Empty containers or liners may retain some product residues. Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers.

Disposal should be in accordance with applicable regional, national and local laws and regulations. Local regulations may be more stringent than regional or national requirements.

The information presented below only applies to the material as supplied. The identification based on characteristic(s) or listing may not apply if the material has been used or otherwise contaminated. It is the responsibility of the waste generator to determine the toxicity and physical properties of the material generated to determine the proper waste identification and disposal methods in compliance with applicable regulations.

Refer to Section 7: HANDLING AND STORAGE and Section 8: EXPOSURE CONTROLS/PERSONAL PROTECTION for additional handling information and protection of employees.

Section 14. Transport information

This Material Safety Data Sheet is written based on the encapsulated substance or mixture in this article. Since the hazardous ingredient is encapsulated, the risk of exposure by inhalation, ingestion, skin contact and eyes contact is minimum.

Additional information

: The environmentally hazardous substance mark is not required when transported in sizes of ≤ 5 L or ≤ 5 kg.

Remarks

Magnetized materials are only considered dangerous goods when offered for transportation by air. Shippers should consult their air carriers prior to offering the shipment for transportation.

Magnetized Materials

Section 14. Transport information

Regulatory information	UN number	Proper shipping name	Classes	PG*	Label	Additional information
DOT	Not regulated.	-	-	III		Reportable quantity 625 lbs / 283.75 kg Package sizes shipped in quantities less than the product reportable quantity are not subject to the RQ (reportable quantity) transportation requirements.
						Remarks Magnetized materials are only considered dangerous goods when offered for transportation by air. USA regulations do not consider magnetized material a hazardous material or dangerous goods. USA domestic shippers should consult USA air carriers policies and procedures prior to offering shipment for transportation.
IMDG	UN2807	MAGNETIZED MATERIAL. Marine pollutant (Aluminium, Copper)	9			The marine pollutant mark is not required when transported in sizes of ≤5 L or ≤5 kg. Special provisions 960

Section 14. Transport information

ΙΑΤΑ	UN2807	Magnetized material	9	The environmentally hazardous substance mark may appear if required by other transportation regulations. Passenger and Cargo Aircraft Packaging instructions: 953 Cargo Aircraft Only Packaging instructions: 953 Limited Quantities - Passenger Aircraft Quantity limitation: Forbidden Packaging instructions: Forbidden

Section 15. Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

U.S. Federal regulations

SARA 302/304

: United States inventory (TSCA 8b): All components are listed or exempted. Clean Water Act (CWA) 307: Nickel; Copper

Clean Air Act Section	
112	: Listed
(b) Hazardous Air	
Pollutants (HAPs)	
Clean Air Act Section 602	: Not listed
Class I Substances	
Clean Air Act Section 602	: Not listed
Class II Substances	
DEA List I Chemicals	: Not listed
(Precursor Chemicals)	
DEA List II Chemicals	: Not listed
(Essential Chemicals)	

Composition/information on ingredients

No products were found.

SARA 304 RQ : Not applicable.

SARA 311/312

Classification

: Immediate (acute) health hazard Delayed (chronic) health hazard Composition/information on ingredients

Magnetized Materials

Section 15. Regulatory information

Name	%	Fire hazard	Sudden release of pressure	Reactive	Immediate (acute) health hazard	Delayed (chronic) health hazard
Cobalt	10 - 30	No.	No.	No.	Yes.	Yes.
Nickel	10 - 30	No.	No.	No.	Yes.	Yes.
Aluminium	5 - 10	Yes.	No.	No.	No.	Yes.
Copper	1 - 5	No.	No.	No.	No.	Yes.

SARA 313

	Product name	CAS number	%
Form R - Reporting	Cobalt	7440-48-4	10 - 30
requirements	Nickel	7440-02-0	10 - 30
	Aluminium	7429-90-5	5 - 10
	Copper	7440-50-8	1 - 5
Supplier notification	Cobalt	7440-48-4	10 - 30
	Nickel	7440-02-0	10 - 30
	Aluminium	7429-90-5	5 - 10
	Copper	7440-50-8	1 - 5

SARA 313 notifications must not be detached from the SDS and any copying and redistribution of the SDS shall include copying and redistribution of the notice attached to copies of the SDS subsequently redistributed. <u>State</u> regulations

Massachusetts	: The following components are listed: COBALT; NICKEL; ALUMINUM; COPPER
New York	: The following components are listed: Nickel; Copper
New Jersey	: The following components are listed: COBALT; NICKEL; ALUMINUM; COPPER; TITANIUM
Pennsylvania	: The following components are listed: COBALT FUME; NICKEL; ALUMINUM; COPPER FUME

California Prop. 65

WARNING: This product contains a chemical known to the State of California to cause cancer.

Ingredient name	Cancer	Reproductive	No significant risk level	Maximum acceptable dosage level
Cobalt	Yes.	No.	No.	No.
Nickel	Yes.	No.	No.	No.

Canada inventory

: All components are listed or exempted.

Section 15. Regulatory information

International regulations	: Australia inventory (AICS): All components are listed or exempted.			
International lists	China inventory (IECSC): All components are listed or exempted.			
	Japan inventory: Not determined.			
	Korea inventory: All components are listed or exempted.			
	Malaysia Inventory (EHS Register): Not determined.			
	New Zealand Inventory of Chemicals (NZIoC): All components are listed or exempted.			
	Philippines inventory (PICCS): Not determined.			
	Taiwan inventory (CSNN): Not determined.			
Chemical Weapons	: Not listed			
Convention List Schedule I Chemicals				
Chemical Weapons	: Not listed			
Convention List Schedule				
II Chemicals				
Chemical Weapons : Convention List Schedule III Chemicals	Not listed			

<u>History</u>	
Date of issue	11/12/2020
Date of previous issue	01/2672017

Version

V Indicates information that has changed from previously issued version.

: 1

Notice to reader

Disclaimer: The information contained in this document is based on Keysight's state of knowledge at the time of preparation. No warranty as to its accurateness, completeness or suitability for a particular purpose is expressed or implied.